

NOTES:

 STAMPED SANDY CITY LOGO AND "STREET LIGHTING" LETTERING INTO THE LID FROM THE MANUFACTURE.


2. DO NOT PLACE JUNCTION BOXES IN DELIBERATE TRAFFIC.

 CONFORM TO ANSI/SCTE-77 2007 "SPECIFICATION FOR UNDERGROUND ENCLOSURE INTEGRITY TIER 22 LOADING FOR ALL JUNCTION BOXES.

 EXTEND GROUND ROD A MINIMUM OF 4 INCHES AND A MAXIMUM OF 6 INCHES ABOVE BOTTOM OF JUNCTION BOX. DO NOT CUT GROUND ROD.

USE A SPLIT BOLT TO ATTACH GROUND WIRES TO 8' GROUND ROD.

6. LID SHALL FASTENED WITH 2 (TWO) STAINLESS STEEL 3/8" PENTAGON HEAD COARSE THREAD BOLT WITH



JUNCTION BOX CONDUIT DETAIL

NOT TO SCALE

CONCRETE OR LANDSCAPE

10"

FOR CONCRETE, USE

COVER

JUNCTION

BOX WALL

EXPANSION JOINT TRIMMED

FLUSH WITH BOTH SURFACES

1	S	CREATED	6/2017	Sandy
NO.	AUTHORIZED BY	REVISIONS	DATE	HEART OF THE WASATCH

STANDARD DETAIL PUBLIC UTILITIES

SL-08

ARTERIAL STREET LIGHT JUNCTION BOX DETAIL